



INSTALLATION GUIDE

FELTON

REGAL OVER THE BATH SHOWER UNIT RW | RWE | RWH

REGAL OVER THE BATH SHOWER UNIT

The Regal is designed to convert an existing bath into a bath/shower. It attaches to existing taps and requires only the simplest of tools.

WHAT IS IN THE PACK

1 x Regal cover (800 x 300mm)	1 x Feltonmix® Mixing Valve & screw pack	1 x Designer II Feltonmix® Wallset White (WWSD2) & screw pack	1 x pipe set (1500mm long pipes with fittings)
	2 x adaptor covers	2 x adaptors with bushes	1 x Screw pack with plastic toggle, cap & cover
			1 x Bag of restrictors with fitting instructions

Warranty, Maintenance and Care YOUR COPY TO KEEP

FELTON

Felton Industries Limited guarantees these mixers to be free from defects in materials and workmanship for a period of five (5) years from the date of purchase. Fair wear and tear is expressly excluded. This warranty is effective for 5 years from the date of purchase for the supply of replacement parts only, not including installation. You must retain proof of purchase of the Mixer (such as an invoice or receipt) and provide this to Felton on request. This warranty is for manufacturing defects only and does not cover any damage to the product due to abuse, negligence or improper installation. This warranty is given on the understanding that the product is installed and operated according to Felton's installation guide and the Australian/New Zealand standard AS/NZS3500. This warranty is provided to persons who are a "consumer" under the Consumer Guarantees Act 1993 only and for use in domestic/residential dwellings only (not for commercial use).

At no stage should any surface coatings be cleaned with cleaning agents that contain a corrosive acid or a scouring additive. Surface coatings should be cleaned with liquid detergent or soap and water. Any damage caused through the use of an unsuitable cleaner will not be covered by this warranty. This warranty is subject to any other rights or remedies that you may have under the Consumer Guarantees Act 1993 (or any other applicable legislation) and to Felton's Terms of Trade.

Please fill in the details below, attach your receipt to this installation guide and keep as your proof of purchase.

Purchased at:

Date of purchase:

Installed by:

For technical assistance please ring: 0800 743 358 or (09) 528 0810

INSTALLATION INSTRUCTIONS

1. Turn off the water at the mains. Remove bath taps and re-install with tap adaptors and covers fitted behind them. Adaptors are provided with a bush to accommodate $\frac{3}{4}$ " or $\frac{1}{2}$ " BSP threads. Seal threads with Ceelon thread tape.
2. Mount shower mixing valve on wall at desired height (not exceeding 1500mm above taps). Add an additional 5-6mm to the calculated pipe length to allow for bends to reach taps.
3. Connect pipes between shower valve isolators and bath tap adaptors. Fit white sleeve at bottom of pipe using long nuts. Connect hot water to red shower valve isolator, cold water to blue. If hot and cold water pipes are reversed, turn shower valve through 180° and rotate isolators to point downwards.
4. Check that there are no leaks to shower valve by closing isolators and turning on mains. Test further for leaks as follows:
 - a. Fit shower handle and turn anticlockwise to OFF position.
 - b. Turn on isolators. All joints must be watertight.
5. To complete installation of shower valve,
 - a. Remove shower handle.
 - b. Remove protective plastic film from Regal cover and fit it and the wallplate to shower valve.
 - c. Fit handle and screw in shower head.
 - d. Attach base of Regal cover using screw, cap and cover supplied. Use plastic toggle if fastening to wallboard, brick or block.
6. For Mains Pressure fit white restrictor using tool as directed into stem of showerhead.

